
2.0DA ACOUSTICAL DOVETAIL ROOF DECK ACOUSTICAL SOLUTIONS

REDUCE INTERIOR NOISE WITH THE SOUND ABSORPTION CAPABILITIES OF 2.0DA ACOUSTICAL ROOF DECK

2.0DA ACOUSTICAL DECK

- 2" Deep Deck
- FM Approved¹
- IAPMO UES ER-423



Noise Reduction Coefficients

		Absorption Coefficients								
Cover Board	Deck Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	RAL Test No.
2" Poly-Iso	Plain	0.19	0.54	1.15	1.07	1.01	0.79	0.95	0.95	<u>A14-170</u>
	Encapsulated	0.35	0.82	1.15	0.99	0.97	0.72	0.96	1.00	<u>A14-167</u>
2" Fiberglass	Plain	0.74	1.40	1.25	1.03	0.98	0.80	1.14	1.15	A14-169
	Encapsulated	0.62	1.18	1.08	0.93	0.97	0.77	1.02	1.05	<u>A14-168</u>
½" Roof Board	Plain	0.17	0.51	1.05	1.05	0.85	0.77	0.85	0.85	A19-101
	Encapsulated	0.30	0.56	1.02	0.99	0.92	0.78	0.86	0.85	A19-102

Notes:

- 1. See Factory Mutual Approval Report for complete assembly details.
- 2. The acoustical test reports with complete assembly details are available from www.dovetaildeck.com.

NOTICE: Design defects that could cause injury or death may result from relying on the information in this document without independent verification by a qualified professional. The information in this document is provided "AS IS". Nucor Corporation and its affiliates expressly disclaim: (i) any and all representations, warranties and conditions and (ii) all liability arising out of or related to this document and the information in it.




3.5DA ACOUSTICAL DOVETAIL ROOF DECK ACOUSTICAL SOLUTIONS

REDUCE INTERIOR NOISE WITH THE SOUND ABSORPTION CAPABILITIES OF 3.5DA ACOUSTICAL ROOF DECK

3.5DA ACOUSTICAL DECK

- 3½" Deep Deck
- FM Approved¹
- IAPMO UES ER-423



Noise Reduction Coefficients

		Absorption Coefficients								
Cover Board	Deck Insulation	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	SSA	NRC	RAL Test No.
2" Poly-Iso	Plain	0.25	0.74	1.13	1.06	0.97	0.75	0.96	1.00	<u>A14-186</u>
	Encapsulated	0.38	0.86	1.18	1.03	0.93	0.65	0.98	1.00	<u>A14-189</u>
2" Fiberglass	Plain	0.92	1.51	1.13	1.06	0.98	0.78	1.14	1.15	<u>A14-187</u>
	Encapsulated	0.97	1.50	1.09	1.00	0.91	0.67	1.10	1.15	<u>A14-188</u>
½" Roof Board	Plain	0.33	0.95	1.20	1.00	0.96	0.74	1.01	1.05	A19-220
	Encapsulated	0.56	1.10	1.13	0.91	0.94	0.64	1.02	1.00	<u>A19-223</u>

Notes:

- 1. See Factory Mutual Approval Report for complete assembly details.
- 2. The acoustical test reports with complete assembly details are available from www.dovetaildeck.com.

NOTICE: Design defects that could cause injury or death may result from relying on the information in this document without independent verification by a qualified professional. The information in this document is provided "AS IS". Nucor Corporation and its affiliates expressly disclaim: (i) any and all representations, warranties and conditions and (ii) all liability arising out of or related to this document and the information in it.

