1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134 Alion Science and Technology

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

TEST REPORT

FOR: Verco Decking, Inc. Phoenix, AZ

CONDUCTED: 20 August 2013

Sound Absorption <u>RAL™-A13-237</u>

Page 1 of 7


ON: #3 N3CD Pan Metal Deck - 1.5 pcf Encapsulated Fiberglass Insulation 5.25" x 1.5" over 2" Poly ISO Board


TEST METHOD

The test method conformed explicitly with the requirements of the ASTM Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method: ASTM C423-09a and E795-05. Riverbank Acoustical Laboratories has been accredited by the U.S. Department of Commerce, National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) for this test procedure (NVLAP Lab Code: 100227-0). A description of the measuring procedure and room qualifications is available separately.

DESCRIPTION OF THE SPECIMEN

The test specimen was designated by the manufacturer as #3 N3CD Pan Metal Deck - 1.5 pcf Encapsulated Fiberglass Insulation 5.25" x 1.5" over 2" Poly ISO Board. A visual inspection by Riverbank staff verified the manufacturer's description, further disclosing a cellular metal deck profile with solid fluted top section and perforated bottom pan. The two elements were shipped loose and assembled with screws. Strips of poly-wrapped 1.5 pcf fiberglass insulation (5.25 in. wide by 1.5 in. thick) were inserted into the entire length of each cell. The entire metal deck specimen was backed by 2 in. thick polyisocyanurate roof board (dense foam panels with reinforced felt facing).





NVLAP Lab Code 100227-0

ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134

Verco Decking, Inc. 20 August 2013

Alion Science and Technology

TEST REPORT

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

<u>RAL^{тм}-A13-237</u> Page 2 of 7

25 Spaces @ 7/32" = 5,5" 7/16 7/32 000 0 0 0 0 0 0 (0 0 0 0 000000 00000 þ 0 0 0 0 0 0 0 (0 0 0 0 0 0 0 0 0 0 0 5/32 PEFFORATED BANDS IN THE ILAT BOTTOM PLATE APPROXIMATELY CENTERED UNDER TOP FLANGES OF 'HE FLUTED TOP SECTION - 5,5" (typ.) -

Flat Pan for N3-CD Acoustical Profiles

Figure 2 - Acoustical perforation detail (supplied by client).

The specimen consisted of 3 pieces laid as a single rectangular patch. The overall dimensions of the specimen as measured were 2.74 m (108.00 in.) wide by 2.44 m (96.00 in.) long and 127.00 mm (5.00 in.) thick. The area used in the calculations was 6.69 m² (72.00 ft²). The weight of the entire specimen as measured was 175.54 kg (387.00 lbs), an average of 26.27 kg/m² (5.38 lbs/ft²).

The specimen was tested in the laboratory's 292.0 m³ (10,311.0 ft³) test chamber. The room temperature at the time of the test was $21\pm0^{\circ}$ C ($70\pm0^{\circ}$ F) and $63\pm1^{\circ}$ relative humidity. The barometric pressure was 744 mm of mercury.



NVLAP Lab Code 100227-0

ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST. This report shall not be reproduced except in full, without the written approval of RAL.

THE RESULTS REPORTED ABOVE APPLY ONLY TO THE SPECIFIC SAMPLE SUBMITTED FOR MEASUREMENT. NO RESPONSIBILITY IS ASSUMED FOR PERFORMANCE OF ANY OTHER SPECIMEN.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134 Alion Science and Technology

TEST REPORT

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

Verco Decking, Inc. 20 August 2013

<u>RAL^{тм}-A13-237</u> Раде 3 of 7



Figure 3 - Specimen mounted in the test chamber.



Figure 4 - Detail of the test specimen.



ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134 Alion Science and Technology

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

<u>RAL^{тм}-A13-237</u> Page 4 of 7

TEST REPORT

Verco Decking, Inc. 20 August 2013

MOUNTING A

The test specimen was laid directly against the test surface. The perimeter was sealed using wood and metal framing.

TEST RESULTS

1/3 Octave Center Frequency (Hz)	Absorption Coefficient	Total Absorption In Sabins
100	0.39	28.38
** 125	0.54	38.99
160	0.65	46.86
200	0.70	50.53
** 250	0.70	50.39
315	0.85	61.52
400	0.92	66.50
** 500	0.92	65.94
630	0.85	60.93
800	0.70	50.43
** 1000	0.67	48.38
1250	0.60	43.31
1600	0.54	39.16
** 2000	0.50	35.94
2500	0.44	31.76
3150	0.40	28.79
** 4000	0.33	24.01
5000	0.33	23.87

SAA = 0.70NRC = 0.70



ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134

Alion Science and Technology

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

TEST REPORT

Verco Decking, Inc. 20 August 2013

RAL™-A13-237 Page 5 of 7

TEST RESULTS (Continued)

The sound absorption average (SAA) is defined as a single number rating, the average, rounded to the nearest 0.01, of the sound absorption coefficient of a material for the twelve one-third octave bands from 200 through 2500 Hz, inclusive.

The noise reduction coefficient (NRC) is defined from previous versions of this same test method as the average of the coefficients at 250, 500, 1000, and 2000 Hz, expressed to the nearest integral multiple of 0.05.

eiabe Approved by_ Tested by *V* Marc Sciaky

Experimentalist

Eric P. Wolfram Laboratory Manager



ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134 Alion Science and Technology

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE


TEST REPORT

Verco Decking, Inc. 20 August 2013

<u>RAL™-A13-237</u> Раде 6 of 7

SOUND ABSORPTION REPORT

#3 N3CD Pan Metal Deck - 1.5 pcf Encapsulated Fiberglass Insulation 5.25" x 1.5" over 2" Poly ISO Board



SAA = 0.70 NRC = 0.70



ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.

1512 S. BATAVIA AVENUE GENEVA, ILLINOIS 60134 Alion Science and Technology

630/232-0104 FOUNDED 1918 BY WALLACE CLEMENT SABINE

TEST REPORT

Verco Decking, Inc. 20 August 2013

<u>RAL™-A13-237</u> Page 7 of 7

Appendix to ASTM C423 Sound Absorption Test Extended Frequency Range Data

Product Description: #3 N3CD Pan Metal Deck - 1.5 pcf Encapsulated Fiberglass Insulation 5.25" x 1.5" over 2" Poly ISO Board (See Full Report)

Riverbank Acoustical Laboratories is accredited to perform sound absorption coefficient measurements for the frequency range of 100Hz to 5,000Hz. However, we calculate sound absorption values at additional test frequencies as a service to our clients.

Although these measurements were made in accordance with the procedures described in ASTM C423-09a, they do not qualify as part of the standard. Since the results are representative of the test environment only, they are unofficial and intended for research and development guidelines rather than for commercial purposes. The sound absorption values at additional frequencies were as follows:

1/3 Octave Center Frequency (Hz)	Absorption <u>Coefficient</u>	Total Absorption (Sabins)
40	0.02	1.30
50	0.08	5.84
63	0.16	11.25
80	0.10	7.31
6300	0.29	21.08
8000	0.32	23.29
10000	0.36	25.99

RAL-A13-237



ACCREDITED BY DEPARTMENT OF COMMERCE, NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM FOR SELECTED TEST METHODS FOR ACOUSTICS. THE LABORATORY'S ACCREDITATION OR ANY OF ITS TEST REPORTS IN NO WAY CONSTITUTES OR IMPLIES PRODUCT CERTIFICATION, APPROVAL, OR ENDORSEMENT BY NIST.